


# ESCP-MIT1

## Medium Isolated MEMS Capacitive Pressure Transmitters



ES Systems has developed a series of medium isolated pressure transmitters suitable for applications with harsh environmental conditions where resistance to corrosive fluids or gases is required. Each sensor integrates a MEMS capacitive pressure sensor die, and a CMOS ASIC for the signal conditioning. The MEMS pressure sensor dies are underpinned by ES Systems' innovative microfabrication process for silicon capacitive sensors.

The ESCP-MIT1 of capacitive pressure sensor dies integrated into the medium isolated pressure systems provide state-of-the-art accuracy and resolution, excellent long-term stability combined with very good repeatability and hysteresis. The total overall error including thermal offsets is lower than  $\pm 0.25\%$  FS.

The ESCP-MIT1 is a family of heavy-duty pressure transmitters made from stainless steel 316L. Each transmitter consists of an ESCP-MIS1 sensor, which is O-ring fitted to the housing. The pressure transmitters come in various standard pneumatic ports as well as custom ones upon request. The electrical interface can be either analog (4-20 mA, 0-10 V) or digital (I<sup>2</sup>C). The sensors can be provided calibrated and compensated at various temperature and pressure ranges from 1 bar to 400 bar. Custom configurations of a variety of pneumatic interfaces, Hastelloy or Titanium material, and output interface are available upon request.



48 Konstantinoupleos str.  
19441 Koropi - Athens, Greece

**T** +30 216 2000500

**F** +30 216 2000555

**info@esenssys.com**

**www.esenssys.com**



# ESCP-MIT1

Medium Isolated  
MEMS Capacitive Pressure Transmitters



## Specifications

<b>Pressure Type</b>	Absolute, Gauge
<b>Pressure Range</b>	Up to 400 bar
<b>Power Supply</b>	+8V ... +32V
<b>Total Error</b>	< ±0.25 %FS
<b>Operating Temperature</b>	-20°C ... +85°C
<b>Compensation Temperature</b>	0°C ... +60°C, -20°C ... +85°C
<b>Digital Output</b>	Calibrated Pressure & Temperature
<b>Analog Output</b>	Calibrated Pressure
<b>Output</b>	4-20mA, 0-10V, I <sup>2</sup> C
<b>Overpressure Tolerance</b>	Up to 100x
<b>Media Compatibility</b>	Gases, Liquids
<b>Material Options</b>	SS 316 L, Hastelloy, Titanium
<b>Connection Type</b>	M12, ISO4400, Cable
<b>Pneumatic Interface</b>	G1/2", G1/4", 1/2" NPT, 1/4" NPT

## Ordering Information

ESCP-MIT1 – NNNNN – NN – NN – NN – NN – NN – N

Pressure Range		Temperature Sensor		Pneumatic Interface		Material		Output Type		Connector		Compensation Temperature	
Absolute	Full Scale	Y	Yes	01	1/2" NPT	01	SS 316 L	01	4-20mA	01	M12	01	0°C to 60°C
002BA	2 bar	N	No	02	1/4" NPT	02	Hastelloy	02	0-10V	02	ISO4400	02	-20°C to 85°C
010BA	10 bar			03	G1/2"	03	Titanium	03	I <sup>2</sup> C (address 0x28)	03	Cable		
015BA	15 bar								04	I <sup>2</sup> C (address 0x29)			
030BA	30 bar								05	I <sup>2</sup> C (address 0x2A)			
050BA	50 bar								06	I <sup>2</sup> C (address 0x2B)			
150BA	150 bar												
250BA	250 bar												
300BA	300 bar												
350BA	350 bar												
400BA	400 bar												



48 Konstantinoupoleos str.  
19441 Koropi - Athens, Greece

T +30 216 2000500

F +30 216 2000555

info@esenssys.com

www.esenssys.com