


ESRF-HF

Insertion Gas Flow Transmitters



ES Systems has developed ESRF-HF, a family of insertion gas flow transmitters, based on the hot-film anemometer principle for mass gas flow measurements.

The ESRF-HF is a family of mass flow transmitters which enable fast and accurate measurements of gas flow over a wide dynamic range. Each transmitter integrates a MEMS flow sensor and readout electronics inside a housing with very small form factor made from stainless steel. The duty pressure of the flow transmitter is 11bar. All measurement data are fully calibrated, and temperature compensated on board, leading to a reduced temperature coefficient and high measurement accuracy.

The standard system provides analog signal output, with excellent repeatability and hysteresis combined with good resolution. Calibration gas is air, but other non-aggressive gases can be also available upon request.

The compact size of the ESRF-HF flow transmitters combined with the ruggedized stainless-steel housing makes them ideal for use in industrial applications within confined spaces. For easier handling and mounting, a series of in-line pipe adaptors (Ø20, Ø25, Ø32) is also available upon request.



57, I. Metaxa str.
19441 Koropi - Athens, Greece

T +30 216 2000500

F +30 216 2000555

info@esenssys.com

www.esenssys.com



ESRF-HF

Insertion Gas Flow Transmitters



Specifications

Calibration Gas	Air, other available on request
Flow Range	Up to 1500 l/min, Unidirectional
Supply Voltage	14 V to 32 V
Output	4-20 mA
Accuracy	± 2 % m.v. + 0.3 % FS.
Resolution	12 bit
Output Update Rate	10 Hz
Duty Pressure	11 bar
Operating Temperature	-40°C ... + 85°C
Calibration Temperature	0°C ... + 50°C
Humidity	0 % - 95 % RH, Non - Condensing
Size (Ø x L)	35 x 56 mm
Pneumatic Interface	Ø20, Ø25, Ø32
Electrical Interface	Cable

Features

- Unidirectional operation
- Wide dynamic range
- Excellent repeatability and hysteresis
- High stability
- High duty pressure
- Low temperature coefficient
- Compact size

Ordering Information

ESRF-HF – XXXX – X – XXXX

Flow Range (l/min)

-0300
-0500
-0800
-1000
-1200
-1500

Gas

-A Air
-O Other

Pneumatic Interface

-Ø20
-Ø25
-Ø32



57, I. Metaxa str.
19441 Koropi - Athens, Greece
T +30 216 2000500
F +30 216 2000555
info@esenssys.com

www.esenssys.com